

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard 29 CFR 1910
 Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form) Form Approved OMB no.1218-0072

Identify (Code Number, Name)

2200190/14

CBC

Section I Manufacturer's Name

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, Fl 33024

Emergency Telephone Number

1-800-228-5635

Telephone # For Information

1-800-253-3500

Date Prepared: 03/19/99

HEALTH**FLAMMABILITY****REACTIVITY**

Protective Equipment

G

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Food Grade Mineral Oil	8042-47-5	5mg/M3	5mg/M3		40-60
Isoparaffinic Hydrocarbon	64741-66-8	400 ppm	400 ppm		20-40
Isoparaffinic Hydrocarbon	64742-48-7	200 ppm	200 ppm		10-20
Carbon Dioxide Propellant	124-38-9	10000 ppm	10000 ppm		01-05

Section III Physical Characteristics

Boiling Point	-300 F	Specific Gravity (Water =1)	0.817
Vapor Pressure	90	Melting Point	N/A
Vapor Density	>1	Evaporation Rate	N/A

Solubility In Water	Emulsifies
Appearance and Odor	Cloudy liquid with solvent odor

Section IV Fire and Explosion Hazard Data

Flash Point	Flammable Limits	LEL	UEL
120 F (TOC)	Flammable Spray		

Extinguishing Media	Foam, Dry Chemical, Carbon Dioxide
----------------------------	------------------------------------