

**Material Safety Data Sheet**

May be used to comply with  
OSHA's Hazard Communication Standard 29 CFR 1910  
Standard must be consulted for specific requirements.

**U.S. Department of Labor**

Occupational Safety and Health Administration  
(Non-Mandatory Form) Form Approved OMB no. 1218-0072

**Identify (Code Number, Name)**

2200865/14

**Chain and Cable Lube Kwik Dri****Section 1 Manufacturer's Name**

**Applied Research, Inc.**  
**7367 Davie Rd. Ext**  
**Hollywood, Fl 33024**

Emergency Telephone Number  
1-800-228-5635

Telephone # For Information  
1-800-253-3500

Date Prepared: 03/12/98

**HEALTH** 1  
**FLAMMABILITY** 4  
**REACTIVITY** 0  
Protective Equipment  
B

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Isoparaffinic Hydrocarbon	64741-66-8	400	400		20-40
Lithium Grease	N/A	N/E	N/E		05-10
Food Grade Mineral Oil	8042-47-5	5mg/m <sup>3</sup> (mist)	5mg/m <sup>3</sup> (mist)		05-10
Aliphatic Mineral Spirits	64742-88-7	100 ppm	100 ppm		01-05
Liquefied Petroleum Gas	68476-85-7	1000 ppm	1000 ppm		40-60

**Section III Physical Characteristics**

<b>Boiling Point</b>	Approx 300 F	<b>Specific Gravity (Water =1)</b>	0.769 (@75 F)
<b>Vapor Pressure</b>	55 (Can/psig @ 70 F)	<b>Melting Point</b>	N/A
<b>Vapor Density</b>	>1	<b>Evaporation Rate</b>	N/A
<b>Solubility In Water</b>	Slight		
<b>Appearance and Odor</b>	Dark Green liquid - Solvent odor		

**Section IV Fire and Explosion Hazard Data**

<b>Flash Point</b>	<b>Flammable Limits</b>	<b>LEL</b>	<b>UEL</b>
40 deg. F (T.O.C.)	Extremely flammable spray	N/A	N/A
<b>Extinguishing Media</b>	Foam, CO2, Dry Media		