

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard 29 CFR 1910
Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form) Form Approved OMB no.1218-0072

Identify (Code Number, Name)

2856001

ESP Light Gray

Section I Manufacturer's Name

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, Fl 33024

Emergency Telephone Number
1-800-228-5635

Telephone # For Information
1-800-253-3500

Date Prepared: 01/24/96

HEALTH 2**FLAMMABILITY** 2**REACTIVITY** 0

Protective Equipment

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Calcium Naphthemat	61789-36-4	No Info	No Info		1.0
Cobalt Naphthemat	61789-51-3	0.1 MG/M3	TLV-TWA-0.05 MG/M3		1.0
Titanium Dioxide	13463-67-7	No Info	TLV-TWA-10 MG/M3		10
Aluminum Hydroxide	21645-51-2	No Info	No Info		0.1
Amorphous Silica	7631-88-9	No Info	No Info		0.1
Zirconium Octoate	22464-99-9	No Info	TLV-TWA-5 MG/M3	TLV-STEL-10 MG/M3	1.0
P M Acetate	108-65-8	No Info	TLV-TWA-100 PPM		1.0
Methyl Ethyl Ketoximine	96-29-7	No Info	No Info		1.0
Methanol	67-58-1	200 PPM	TLV-TWA-200 PPM	TLV-STEL-250 PPM	1.00
Xylene	1330-20-7	100 PPM	TLV-TWA-100 PPM	TLV-STEL-150 PPM	5
Mineral Spirits	64741-92-0	No Info	TLV-TWA-100 PPM	TLV-STEL-200 PPM	45
This product contains one or more materials subject to the reporting requirements of Section 313 of the Emergency Planning and the Community Right-To-Know Acts of 1986 and of 40 CFR 372.					

Section III Physical Characteristics

Boiling Point	283-390 deg F	Specific Gravity (Water =1)	
Vapor Pressure		Melting Point	
Vapor Density	Heavier than air	Evaporation Rate	Slower than other