

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard 29 CFR 1910
Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form) Form Approved OMB no.1218-0072

Identify (Code Number, Name)

1250705

Graffiti Gone**Section I Manufacturer's Name**

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, Fl 33024

Emergency Telephone Number
1-800-253-3500

Telephone # For Information
1-800-253-3500

Date Prepared: 01/29/99

HEALTH 3**FLAMMABILITY** 2**REACTIVITY** 0

Protective Equipment

X

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Potassium Hydroxide	1310-58-3	2 mg/m3	2 mg/m3		
Sodium Hydroxide	1310-73-2	2 mg/m3	N/A		
Monoethanolamine	141-43-5	3 ppm	3 ppm		
Propylene Glycol Monomethyl Ether	107-98-2	100 ppm	100 ppm		
Dipropylene Glycol Monomethyl Ether	34590-94-8	100 ppm	100 ppm		
Diethylene Glycol Monoethyl Ether	111-90-0	N/A	N/A		12

Section III Physical Characteristics

Boiling Point	N/A	Specific Gravity (Water =1)	>1
Vapor Pressure	N/A	Melting Point	N/A
Vapor Density	>1	Evaporation Rate	<1

Solubility In Water	Complete
Appearance and Odor	Light amber, viscous liquid, characteristic odor

Section IV Fire and Explosion Hazard Data

Flash Point	Flammable Limits	LEL	UEL
143 Deg. F.			

Extinguishing Media	Water, foam, CO2
----------------------------	------------------

Special Fire Fighting Self-contained breathing apparatus and special clothing should be worn by firefighters.