

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard 29 CFR 1910
Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form) Form Approved OMB no. 1218-0072

Identify (Code Number, Name)

2851240

Great Dane Concrete Seal**Section 1 Manufacturer's Name**

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, FL 33024

Emergency Telephone Number
1-800-228-5635

Telephone # For Information
1-800-253-3500

Date Prepared: 09/02/98

HEALTH 2**FLAMMABILITY** 2**REACTIVITY** 0

Protective Equipment

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
1,10-Phenanthroline	66-71-7	No Info	No Info		0.1
N-Butyl Alcohol	71-36-35	No Info	50 ppm		0.1
2-Ethylhexanoic Acid	149-57-5	No Info	No Info		0.1
Manganese Napthenate	61788-57-6	No Info	5 MG/M3		0.1
Methyl Ethyl Ketoximine	96-29-7	No Info	No Info		1.0
Mineral Spirits	64741-92-0	No Info	100 ppm		65

Section III Physical Characteristics

Boiling Point	318-383 F	Specific Gravity (Water =1)	N/A
Vapor Pressure	N/A	Melting Point	N/A
Vapor Density	Heavier than air	Evaporation Rate	Slower than ether

Solubility In Water	None
Appearance and Odor	Light yellow clear with mineral spirits odor.

Section IV Fire and Explosion Hazard Data

Flash Point	Flammable Limits	LEL	UEL
104 F (tagliabue closed cup)		0.7	6.0

Extinguishing Media	Dry chemical, carbon dioxide, foam.
----------------------------	-------------------------------------