

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard 29 CFR 1910
 Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form) Form Approved OMB no. 1218-0072

Identify (Code Number, Name)

1254511

Green Slime (100)**Section I Manufacturer's Name**

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, Fl 33024

Emergency Telephone Number
 1-800-228-5635

Telephone # For Information
 1-800-253-3500

Date Prepared: 09/11/97

HEALTH 1**FLAMMABILITY** 2**REACTIVITY** 0

Protective Equipment

B

| Hazardous Components (Specify Chemical Identity, Common Name) | CAS # | OSHA PEL | ACGIH TLV | Other Recommended Limits | % |
|---|-----------|-------------|------------------------|--------------------------|---|
| d-Limonene | 5989-27-5 | LPR-MUS TD: | 4800mg/kg/ 8W-1:ETA | | |
| | | ORL-MUS TD: | 67 gm/kg/ 39W-1:ETA | | |
| | | | | | |
| | | | | | |
| | | | | | |
| DOT Shipping Classification: Combustible Liquid | | | | | |

Section III Physical Characteristics

| | | | |
|---------------------|---|-----------------------------|------|
| Boiling Point | 310 deg F | Specific Gravity (Water =1) | 0.84 |
| Vapor Pressure | 1.9 mm HG @ 20 C | Melting Point | NA |
| Vapor Density | .012 | Evaporation Rate | <1 |
| Solubility In Water | Miscible | | |
| Appearance and Odor | Clear to pale yellow liquid. Strong orange scent. | | |

Section IV Fire and Explosion Hazard Data

| | | | |
|-------------|------------------|-----|-----|
| Flash Point | Flammable Limits | LEL | UEL |
| 115 F | | 0.7 | 6.1 |

| | |
|---------------------|------------------------------------|
| Extinguishing Media | Foam, carbon dioxide, dry chemical |
|---------------------|------------------------------------|