

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard 29 CFR 1910
Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form) Form Approved OMB no. 1218-0072

Identify (Code Number, Name)**2200427/19****Kleer Vue****Section 1 Manufacturer's Name**

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, Fl 33024

Emergency Telephone Number
1-800-228-5635

Telephone # For Information
1-800-253-3500

Date Prepared: 12/21/98

HEALTH **1**
FLAMMABILITY **1**
REACTIVITY **0**
Protective Equipment
A

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Isopropyl Alcohol	67-63-0	400 ppm	400 ppm		05-10
Liquefied Petroleum Gas	68476-85-7	1000 ppm	1000 ppm		05-10

Section III Physical Characteristics

Boiling Point	-212 F	Specific Gravity (Water =1)	0.978 @ 75 F
Vapor Pressure	(can/psig @ 70 F): 55	Melting Point	N/A
Vapor Density	>1	Evaporation Rate	N/A

Solubility In Water	Complete
Appearance and Odor	White Foam

Section IV Fire and Explosion Hazard Data

Flash Point	Flammable Limits	LEL	UEL
None to Boiling (212 F) (Concentrate Only) Non- flammable Spray	N/A	N/A	N/A

Extinguishing Media	Foam, CO2, Dry Media
----------------------------	----------------------