

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard 29 CFR 1910
Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form) Form Approved OMB no. 1218-0072

Identify (Code Number, Name)

1250197

Kold Kut H.D.**Section I Manufacturer's Name**

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, Fl 33024

Emergency Telephone Number
1-800-228-5635

Telephone # For Information
1-800-253-3500

Date Prepared: 03/14/95

HEALTH 1
FLAMMABILITY 1

REACTIVITY 0

Protective Equipment

H

| Hazardous Components (Specify Chemical Identity, Common Name) | CAS # | OSHA PEL | ACGIH TLV | Other Recommended Limits | % |
|---|------------|----------|-----------|--------------------------|---|
| Hydrotreated heavy naphthenic distillate, petroleum | 64742-52-5 | 5mg/m3 | 5mg/m3 | | |
| Proprietary additives | | N/A | N/A | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |

Section III Physical Characteristics

| | | | |
|-----------------------|------------------------|------------------------------------|-------|
| Boiling Point | 520 Deg. F. | Specific Gravity (Water =1) | 0.9 |
| Vapor Pressure | <0.01mm Hg @ 20 Deg. C | Melting Point | N/A |
| Vapor Density | >5 | Evaporation Rate | <0.01 |

| | |
|----------------------------|--|
| Solubility in Water | Emulsifiable |
| Appearance and Odor | Clear, dark amber liquid, mild, bland petroleum odor |

Section IV Fire and Explosion Hazard Data

| | | | |
|--------------------|-------------------------|------------|------------|
| Flash Point | Flammable Limits | LEL | UEL |
| 315 Deg. F (COC) | | 0.9 | 7.0 |

| | |
|----------------------------|--|
| Extinguishing Media | Foam, water spray, dry chemical, carbon dioxide and vaporizing liquid type extinguishing agents may all be suitable. |
|----------------------------|--|