

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard 29 CFR 1910
Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form) Form Approved OMB no. 1218-0072

Identify (Code Number, Name)

2200722/15

Protect**Section I Manufacturer's Name**

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, Fl 33024

Emergency Telephone Number
1-800-228-5635

Telephone # For Information
1-800-253-3500

Date Prepared: 03/16/98

HEALTH 1
FLAMMABILITY 4

REACTIVITY 0

Protective Equipment
B

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Isoparaffinic Hydrocarbon	64742-48-9	400 ppm	400 ppm		10-20
Oxygenated Hydrocarbon Blend	N/A	N/E	N/E		40-60
Liquefied Petroleum Gas	68476-85-7	1000 ppm	1000 ppm		20-40

Section III Physical Characteristics

Boiling Point N/D	Specific Gravity (Water =1) @ 75 deg F: 0.730
Vapor Pressure (can) psig @ 70 deg F: 50	Melting Point
Vapor Density >1	Evaporation Rate
Solubility In Water Slight	
Appearance and Odor	Dark brown liquid, solvent odor

Section IV Fire and Explosion Hazard Data

Flash Point	Flammable Limits	LEL	UEL
(Concentrate): 45 deg F (T.O.C.)	Extremely flammable spray		

Extinguishing Media	Foam, CO2, Dry Media
----------------------------	----------------------