

**Material Safety Data Sheet**

May be used to comply with  
OSHA's Hazard Communication Standard 29 CFR 1910  
Standard must be consulted for specific requirements.

**U.S. Department of Labor**

Occupational Safety and Health Administration  
(Non-Mandatory Form) Form Approved OMB no.1218-0072

**Identify (Code Number, Name)**

2859002

RBE Non-Skid Gray

**Section I Manufacturer's Name**

**Applied Research, Inc.**  
**7367 Davie Rd. Ext**  
**Hollywood, Fl 33024**

Emergency Telephone Number  
1-800-228-5635

Telephone # For Information  
1-800-253-3500

Date Prepared: 08/17/98

**HEALTH** 2  
**FLAMMABILITY** 0  
**REACTIVITY** 0  
Protective Equipment

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Cristobalite	14464-46-1	.05 MG/M3	.05 MG/M3		5
Titanium Dioxide	13463-67-7	No Info	10MG/M3 (TWA)		5
Aluminum Hydroxide	21645-51-2	No Info	No Info		0.1
Amorphous Silica	7631-86-9	No Info	No Info		0.1
Silicon Dioxide	14808-60-7	No Info	0.1MG/M3 (TWA)		45
Aromatic Petroleum Distillates	64742-95-6	No Info	No Info		15
Trimethylbenzenes	25551-13-7	No Info	No Info		10
Chlorinated Paraffin	61788-76-9	No Info	No Info		1.0
Carbon Black	1333-86-4	No Info	3.5MG/M3 (TWA)		1.0
(SEE ADENDUM)					

**Section III Physical Characteristics**

<b>Boiling Point</b>	318-383 F	<b>Specific Gravity (Water =1)</b>	N/A
<b>Vapor Pressure</b>	N/A	<b>Melting Point</b>	N/A
<b>Vapor Density</b>	Heavier than air	<b>Evaporation Rate</b>	Slower than ether

<b>Solubility In Water</b>	None
<b>Appearance and Odor</b>	Opaque, Gray with typical solvent odor

**Section IV Fire and Explosion Hazard Data**

<b>Flash Point</b>	<b>Flammable Limits</b>	<b>LEL</b>	<b>UEL</b>
105 F (Cleveland Open Cup)	N/A	N/A	N/A

<b>Extinguishing Media</b>	Dry chemical, Carbon Dioxide, Foam
----------------------------	------------------------------------