

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard 29 CFR 1910
Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form) Form Approved OMB no.1218-0072

Identify (Code Number, Name)

1250620

Root-B-Gone**Section 1 Manufacturer's Name**

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, Fl 33024

Emergency Telephone Number
1-800-228-5635

Telephone # For Information
1-800-253-3500

Date Prepared: 03/20/97

HEALTH 3**FLAMMABILITY** 0**REACTIVITY** 1

Protective Equipment

x

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Anhydrous Sodium Hydroxide	1310-73-2	2mg/m ³	2mg/m ³	200 ppm (IDLH)	
DOT Shipping Classification: Dry solid corrosive Material UN 1823					

Section III Physical Characteristics

Boiling Point	1390 deg C	Specific Gravity (Water =1)	2.13
Vapor Pressure	NA	Melting Point	NA Vapor
Vapor Density	NA	Evaporation Rate	NA

Solubility In Water	347 G/100 G Water @ 100 deg C (Butyl Acetate=1)
Appearance and Odor	White to slightly colored solid. No odor

Section IV Fire and Explosion Hazard Data

Flash Point	Flammable Limits	LEL	UEL
None	NA	NA	NA

Extinguishing Media	NA
----------------------------	----