

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard 29 CFR 1910
 Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form) Form Approved OMB no.1218-0072

Identify (Code Number, Name)
1250408

Tar & Asphalt Remover**Section I Manufacturer's Name**

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, Fl 33024

Emergency Telephone Number
 1-800-228-5635

Telephone # For Information
 1-800-253-3500

Date Prepared: 04/09/99

HEALTH 1

FLAMMABILITY 1

REACTIVITY 0

Protective Equipment

A

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Petroleum Naptha	8052-41-3	500 ppm	500 ppm	N/A	
Dipropylene Glycol Methyl Ether	34590-94-8	100 ppm	100 ppm	N/A	

Section III Physical Characteristics

Boiling Point	330-390 deg F	Specific Gravity (Water =1)	< 1.0
Vapor Pressure	<10 @ 77 deg F	Melting Point	N/A
Vapor Density	4.8	Evaporation Rate	< 1.0

Solubility In Water	Neglible
Appearance and Odor	Clear Liquid, Characteristic Solvent Odor

Section IV Fire and Explosion Hazard Data

Flash Point	Flammable Limits	LEL	UEL
105-114 deg F	Non-Flammable	1	6

Extinguishing Media	Water Fog, Foam, Dry Chemical or Carbon Dioxide
Special Fire Fighting	Self contained breathing apparatus and full bunker gear recommended for firefighters. Water may