

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard 29 CFR 1910
Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form) Form Approved OMB no. 1218-0072

Identify (Code Number, Name)

3300088

Total Kill**Section I Manufacturer's Name**

Emergency Telephone Number
1-800-228-5635

HEALTH 2
FLAMMABILITY 2

Applied Research, Inc.
7367 Davie Rd. Ext
Hollywood, Fl 33024

Telephone # For Information
1-800-253-3500

REACTIVITY 2
Protective Equipment

Date Prepared: 03/15/95

Hazardous Components (Specify Chemical Identity, Common Name)	CAS #	OSHA PEL	ACGIH TLV	Other Recommended Limits	%
Bromacil			N/A		0.98
2,4-Dichlorophenoxyacetic acid, isooctyl ester	94-75-7		N/A		1.09
Petroleum distillates					95.83
EPA REG. NO. 8123-29					
DOT HAZARDOUS MATERIALS DESCRIPTION:					
Combustible Liquid, N.O.S. (Petroleum Distillate) PGIII NA 1993					

Section III Physical Characteristics

Boiling Point	350-500 deg F (range)	Specific Gravity (Water =1)	0.85-0.90
Vapor Pressure	0.3 mm Hg	Melting Point	N/A
Vapor Density	Greater than 1	Evaporation Rate	Less than 1
Solubility In Water	Negligible		
Appearance and Odor	Tan to brown liquid; petroleum odor		

Section IV Fire and Explosion Hazard Data

Flash Point	Flammable Limits	LEL	UEL
150 deg F (TCC)		Approx. 1.0	Approx. 7.0